

WUNDER-COVER


WC6060DS - SINGLE LID WUNDER-COVER

The WC6060DS is our most popular recessed infill access cover. The galvanised steel frame and removable tray accept pavers, tiles, cobblestones, concrete, or landscaping materials - making manholes and utility access points virtually invisible while maintaining full access for maintenance.

KEY FEATURES

- **NZ Made**
Manufactured locally with custom sizing available
- **Trafficable**
Load rating tested to 25 tonnes
- **Hot-Dipped Galvanised**
Stainless steel also available
- **Lightweight**
Only 31.68kg pre-installation
- **Easy Installation**
Simple 4-step process with standard tools
- **Versatile Surfaces**
Infill to match the surrounding surface
- **Neoprene Seal**
Keep gases in and unwanted material out
- **Easy Removal**
Tilt-and-slide operation using standard lifting keys

TECHNICAL DRAWING



Extended technical drawings with measurements on page 2

STOCKED SINGLE-LID WUNDER-COVERS

- WC4545AS** 450 × 450 × 100mm
- WC6060DS** 600 × 600 × 100mm

Custom sizes to order on request

TECHNICAL SPECIFICATIONS

Product Code:	WC6060DS
Seal:	Compressible neoprene
Material:	Hot-dipped galvanised steel
Alt. Material:	316 Stainless steel
Standard Depth:	100mm (custom available on request)
Load Rating:	Trafficable
Lid Weight:	13.87kg (empty)
Total Weight	31.68kg (lid + frame)
Removal:	Standard lifting keys using a tilt-slide operation
Shipping Dimensions:	800 × 800 × 100mm

INSTALLATION NOTES

- All work must be completed in a tradesman-like manner
- Frame must be fully supported including internal flanges and gussets
- Set frame to desired level, oriented to suit paver pattern or surrounding surface
- Plaster all gaps; leave sufficient depth for pavers over external flanges
- Tiles/asphalt can be set with partial concrete fill for added stability
- Contact us for advice on unusually heavy loads or custom applications

Created On: 13/03/2023 DO NOT SCALE

Quantity

ITEM NO.	PART NUMBER	QTY.
1	WC6060DS Frame Sides	4
2	M10 rivnut	16
3	WC6060DS Support Angle	4
4	WC6060DS Tray Assembly-RevC	1
5	M10 x 20 Button Head	16
6	Foam Strip 600	2
7	Foam Strip 582	2

Sheet 1 of 2

Rev	Modification	Date	By	Material	mm	CUSTOMER	Date	2/09/2013	TITLE	
C	Changed to Side welded lift lug	21/05/14	SM	Finish	Scale 1:10	Weight: 31.85Kg		SM	WC6060DS Assembly-C	
<small>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ADVANCED TRAFFIC SUPPLIES LTD. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ADVANCED TRAFFIC SUPPLIES LTD IS PROHIBITED.</small>							Units in Millimetres		DWG NO: WC6060DS Assembly-C	Rev: C

Created On: 13/03/2023 DO NOT SCALE

Quantity

800 O/A Unit Size
 606 O/A Frame Size

591 Inside Tray Size

600 Inside Frame size

18 x 9 Adhesive Foam Strip

E-E (1 : 5)

100 O/A Frame Depth

92 Inside Tray Depth

Sheet 2 of 2

Rev	Modification	Date	By	Material	mm	CUSTOMER	Date	2/09/2013	TITLE	
C	Changed to Side welded lift lug	21/05/14	SM	Finish	Scale 1:10	Weight: 31.10Kg	ATS	SM	WC6060DS Assembly-C-Exploded	
<small>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ADVANCED TRAFFIC SUPPLIES LTD. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ADVANCED TRAFFIC SUPPLIES LTD IS PROHIBITED.</small>							Units in Millimetres		DWG NO: WC6060DS Assembly-C	Rev: C

Created On: 4/10/2023 DO NOT SCALE

Quantity

Sheet 1 of 2

REVISIONS		Material	mm	CUSTOMER	Date	TITLE	
REV.	DESCRIPTION	DATE	By		21/07/2013	WC6060DS Tray Assembly-RevC	
					Name	SM	
		Scale	1:10	Weight	13.87Kg		
		Router No:			Units in	Millimetres	
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ADVANCED TRAFFIC SUPPLIES LTD. ANY REPRODUCTION IN WHOLE OR IN PART WITHOUT THE WRITTEN PERMISSION OF ADVANCED TRAFFIC SUPPLIES LTD IS PROHIBITED.						DWG NO: WC6060DS Tray Assembly-RevC	
						Rev:	