

WUNDER-GRATE


WG6060 - RECESSED INFILL DRAINAGE GRATE

The WG6060 is our standard recessed infill drainage grate. The steel frame and removable tray accept pavers, tiles, or surrounding surface materials - blending drainage points seamlessly with surrounding surfaces while maintaining water flow through slotted openings.

KEY FEATURES

- **NZ Made**
Manufactured locally with custom sizing available
- **Slotted Drainage**
Maintains water flow through designed openings
- **Hot-Dipped Galvanised**
Stainless steel also available
- **Lightweight for Size**
Only 33.69Kg total weight (unfilled)
- **Easy Installation**
Simple process with standard tools
- **Versatile Surfaces**
Infill to match the surrounding surface
- **Easy Removal**
Standard utility lifting keys

TECHNICAL DRAWING



Extended technical drawings with measurements on page 2

STANDARD WUNDER-GRATE SIZES

WG3030 300 × 300 × 100mm
WG6060 600 × 600 × 100mm

Custom sizes to order on request

TECHNICAL SPECIFICATIONS

| | |
|-----------------------------|--|
| Product Code: | WG6060 |
| Drainage Slot: | 20mm |
| Material: | Hot-dipped galvanised steel |
| Alt. Material: | 316 Stainless steel |
| Standard Depth: | 100mm (custom available) |
| Load Rating: | Light vehicle traffic |
| Lid Weight: | 12.35Kg (empty) |
| Total Weight: | 33.69kg (lid + frame) |
| Removal: | Standard lifting keys using a tilt-slide operation |
| Shipping Dimensions: | 800 × 800 × 100mm |

INSTALLATION NOTES

- All work must be completed in a tradesman-like manner
- Frame must be fully supported on surrounding surface
- Set frame to desired level, oriented to suit drainage fall
- Ensure drainage slots remain clear and unobstructed
- Contact us for advice on custom applications

