

WUNDER-GRATE


WG6060 - RECESSED INFILL DRAINAGE GRATE

The WG6060 is our standard recessed infill drainage grate. The steel frame and removable tray accept pavers, tiles, or surrounding surface materials - blending drainage points seamlessly with surrounding surfaces while maintaining water flow through slotted openings.

KEY FEATURES

- **NZ Made**
Manufactured locally with custom sizing available
- **Slotted Drainage**
Maintains water flow through designed openings
- **Hot-Dipped Galvanised**
Stainless steel also available
- **Lightweight for Size**
Only 33.69Kg total weight (unfilled)
- **Easy Installation**
Simple process with standard tools
- **Versatile Surfaces**
Infill to match the surrounding surface
- **Easy Removal**
Standard utility lifting keys

TECHNICAL DRAWING



Extended technical drawings with measurements on page 2

STANDARD WUNDER-GRATE SIZES

WG3030 300 × 300 × 100mm

WG6060 600 × 600 × 100mm

Custom sizes to order on request

TECHNICAL SPECIFICATIONS

Product Code:	WG6060
Drainage Slot:	20mm
Material:	Hot-dipped galvanised steel
Alt. Material:	316 Stainless steel
Standard Depth:	100mm (custom available)
Load Rating:	Light vehicle traffic
Lid Weight:	12.35Kg (empty)
Total Weight:	33.69kg (lid + frame)
Removal:	Standard lifting keys using a tilt-slide operation
Shipping Dimensions:	800 × 800 × 100mm

INSTALLATION NOTES

- All work must be completed in a tradesman-like manner
- Frame must be fully supported on surrounding surface
- Set frame to desired level, oriented to suit drainage fall
- Ensure drainage slots remain clear and unobstructed
- Contact us for advice on custom applications

